



# 160 Watt Series

Desktop Type

ATS160T - P X X X

P : C6 / C14 ← → O / P Voltage

## Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI

No Load Power Consumption Less Than 0.15W

## Features :

- IEC/EN/UL 62368-1 & 60950-1
- 100-240VAC Universal Input
- Single Output to 160W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

## Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / RCM / CCC

## Electrical

Topology	LLC
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3Pin
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI Certified
EMC Standards	EN55032
	EN61000-3-2,3
	EN55024
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Model	O/P Voltage	O/P Current	Watt
ATS160T-P120	12.0V	12.50A	150W
ATS160T-P150	15.0V	10.00A	150W
ATS160T-P190	19.0V	8.40A	160W
ATS160T-P240	24.0V	6.60A	160W
ATS160T-P480	48.0V	3.30A	160W
ATS160T-P560	56.0V	2.86A	160W

## Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.2A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C14

## Output

Load Regulation	±5% ( Typical )
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2095 / UL 2464 / 16AWG / 18AWG
Ferrite Core	No (Optional)

## Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

## Mechanical

Case Dimension	L 175 × W 74 × H 42 (mm)
Weight	700g (Ref.)