


**NEW**

**Level VI**

# 160 Watt Medical Series

Desktop Type



**ATM160T - P X X X**

P : C6 / C14 ← → O / P Voltage

**Green Mode**  
 Meet CEC, DoE Level VI, Energy Star, ErP Stage 2  
 No Load Power Consumption Less Than 0.15W

- Features :**
- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)
  - EMC : IEC60601-1-2 : 2014 (edition 4.0)
  - IEC 60950 approval
  - Means of Protection: 2 X MOPP
  - Touch Current : < 100µA
  - 100-240VAC Universal Input
  - Single Output to 160W
  - Regulated Output With Low Ripple Noise
  - Safety Agency Requirements and EMI/EMS Certified
  - Private Label Marking Available
  - Modified and Custom Design Available
  - 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM160T-P120	12.0V	12.5A	150W
ATM160T-P190	19.0V	8.4A	160W
ATM160T-P240	24.0V	6.6A	160W
ATM160T-P480	48.0V	3.3A	160W

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.8A-0.9A
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C14

Output	
Load Regulation	±5% ( Typical )
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2464 / 16AWG
Ferrite Core	NO( Optional )

**Safety Approvals**  
 CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE

Electrical	
Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2 Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental	
Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical	
Case Dimension	L 183 × W 81 × H 42 (mm) ( Ref. )
Weight	820 g ( Ref. )