

NEW
Level VI

300 Watt Medical Series

Desktop Type

ATM300T - P X X X

P : C14 ← → O / P Voltage



Green Mode
Meet CEC, DoE Level VI, Energy Star, ErP Stage 2
No Load Power Consumption Less Than 0.5W

- Features :**
- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)
 - EMC : IEC60601-1-2 : 2014 (edition 4.0)
 - IEC 60950 approval
 - Means of Protection: 2 X MOPP
 - Touch Current : < 100µA
 - 100-240VAC Universal Input
 - Single Output to 300W
 - Regulated Output With Low Ripple Noise
 - Safety Agency Requirements and EMI/EMS Certified
 - Private Label Marking Available
 - Modified and Custom Design Available
 - 2 Years Warranty

Output	
Load Regulation	±5% (Typical)
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2464
Ferrite Core	NO(Optional)

Safety Approvals
CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE

Electrical	
Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2 Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Model	O/P Voltage	O/P Current	Watt
ATM300T-P120	12.0V	24.00A	288W
ATM300T-P190	19.0V	15.78A	300W
ATM300T-P240	24.0V	12.50A	300W
ATM300T-P480	48.0V	6.25A	300W

Environmental	
Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	3.4A-1.6A
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C14

Mechanical	
Case Dimension	L 254 × W 116 × H 47 (mm) (Ref.)
Weight	1600 g (Ref.)

