



36 Watt Medical Series

Desktop Type

ATM036T - □ X X X

P: C6 / C14 -A: C8/C18

► O / P Voltage









Green Mode

Meet CEC, DoE Level VI, Energy Star, ErP Stage 2 No Load Power Consumption Less Than 0.075W

Features:

■ ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)

■ EMC : IEC60601-1-2 : 2014 (edition 4.0)

■ IEC 60950 approval

■ Means of Protection: 2 X MOPP

■ Touch Current: < 100µA

■ 100-240VAC Universal Input

■ Single Output to 36W

■ Regulated Output With Low Ripple Noise

■ Safety Agency Requirements and EMI/EMS Certified

■ Private Label Marking Available

■ Modified and Custom Design Available

■ 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM036T-□050	5.0V	5.00A	25W
ATM036T-□075	7.5V	4.00A	30W
ATM036T-□090	9.0V	4.00A	36W
ATM036T-□120	12.0V	3.00A	36W
ATM036T-□150	15.0V	2.40A	36W
ATM036T-□180	18.0V	2.00A	36W
ATM036T-□240	24.0V	1.50A	36W

100-240VAC
50-60Hz
1.0A-0.45A
Internal Primary Current Fuse
IEC60320/C6, C8, C14, C18

Output	
Load Regulation	±5% (Typical)
Ripple	2% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	20AWG / 18AWG / 16AWG
Ferrite Core	Yes

Safety Approvals

CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE

Electrical		
Topology	Switching Flyback	
Dielectric Withstand	4000VAC Primary - Secondary	
Touch Current	< 100µA	
Efficiency	DoE Level VI, Energy Star, ErP Stage 2 Certified	
EMI Conduction & Radiation	Compliance to EN55011 Class B	
Harmonic Current	Compliance to EN61000-3-2, 3	
EMS Immunity	Compliance to IEC60601-1-2	
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332	
Environmental		
Operating Temperature	0 to + 40°C	
Storage Temperature	-20 to + 80°C	
Relative Humidity	Operating : 20 to 80% RH	
	Storage: 10 to 90% RH	
Cooling	Natural Convection Cooling	
Mechanical		
Case Dimension	L 100 × W 50 × H 33 (mm) (Ref.)	
Weight	210 g (Ref.)	



