



**NEW**

**Level VI**

**CoC Tier 2**

# 90 Watt Series

Desktop Type

ATS090T - P X X X

P : C6 / C14 ← → O / P Voltage

### Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI  
No Load Power Consumption Less Than 0.15W

### Features :

- 100-240VAC Universal Input
- Single Output to 90W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Output	
Load Regulation	±5% ( Typical )
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	20AWG / 18AWG / 16AWG
Ferrite Core	Yes

### Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / LPS

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3 Pin
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to IEC61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	C6 - L 139 × W 61 × H 36 (mm) C14 - L 151 × W 64 × H 36 (mm)
Weight	460 g ( Ref. )

Model	O/P Voltage	O/P Current	Watt
ATS090T-P120	12.0V	7.00A	84W
ATS090T-P150	15.0V	6.00A	90W
ATS090T-P160	16.0V	5.63A	90W
ATS090T-P180	18.0V	5.00A	90W
ATS090T-P190	19.0V	4.74A	90W
ATS090T-P200	20.0V	4.50A	90W
ATS090T-P240	24.0V	3.75A	90W
ATS090T-P300	30.0V	3.00A	90W
ATS090T-P480	48.0V	1.88A	90W
ATS090T-P560	56.0V	1.60A	90W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.2A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6,C14