

**NEW**

**I.T.E.**



# 200 Watt Series

Desktop Type

ATS200A1 - □ X X X

G : C6 ← P : C14 → O / P Voltage



### Features :

- IEC/EN/UL 62368-1 3rd Edition
- 100-240VAC Universal Input
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS200A1-□120	12.0V	16.00A	192W
ATS200A1-□190	19.0V	10.50A	200W
ATS200A1-□240	24.0V	8.30A	200W
ATS200A1-□480	48.0V	4.17A	200W
ATS200A1-□560	56.0V	3.58A	200W

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.4 A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C14

Output	
Load Regulation	±5% ( Typical )
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Electrical	
Topology	LLC
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3Pin
Efficiency	DoE Level VI, ErP Stage 2
EMC Standards	EN55032
	EN61000-3-2,3
	EN55035
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental	
Operating Temperature	-20 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical	
Case Dimension	L 175.2 × W 74 × H 42 (mm)
Weight	738g (Ref.)



R33154 RoHS RoHS